



IP30 Class 1

E-LED/M/S14 E-LED/M/D21

**WALL/CEILING MOUNT
SLIM L.E.D. EXIT SIGN**



TYPE AND BATCH Tested with PSB PLS- LISTED Label

HIGH BRIGHTNESS WHITE L.E.D.
(Lighting Emitting Device)
Consumption <1 Watt

- Mode of Operation : Maintained.
- Rated Duration : > 3 hrs
- Input Supply : 230 Volt, 50Hz / 60Hz
- Battery : High temperature nickel cadmium rechargeable battery
- Charger : Fully automatic solid state Electronics. Constant current limiting with Trickle Charge Facility
- Charge Monitor : Red L.E.D. Ø5mm to indicate charging
- Test Facility : Push-Off test switch to simulate power failure
- Safety Feature : Low voltage cut-off device to prevent over-discharge of battery
- Construction : Plastic/Aluminium
- Diffuser : Fire retardant acrylic
- Legend : ISO green, other legend optional
- Mounting : Wall or ceiling
- Cable Entry : Ø19mm K/O hole
- Weight : Approximate 1.7kg (Gross) for single sided
2.0kg (Gross) for double sided
- Compliance : CP19, SS 263:Part 2,
IEC 598-2-22, SS 364
EMC : EN55015 : 1996
- Dimension : 383 x 252 x 50 mm



Not Radiative

No specialised Disposal required

ADVANTAGES

- low heat
- low consumption
- low maintenance
- high durability
- no "black ends"
- longer duration



- Comply to year 2004 PSB requirements
- Comply to EMC requirements

Ordering Guide

Legend	Maintained Mode	
	SINGLE FACE	DOUBLE FACE
EXIT	E-LED/M/S14	E-LED/M/D21
◀EXIT	E-LED/M/S14L	E-LED/M/D21L
EXIT▶	E-LED/M/S14R	E-LED/M/D21R

*specifications subject to changes without prior notices.